

9200 Series
Mullions



9200 SERIES Mullions

SUGGESTED ARCHITECTURAL SPECIFICATIONS

The PDQ/AE 9200 series keyed removeable mullions are for use with our 4200 and 6200 series Rim Exit Devices on non fire or fire rated pairs of doors. They are designed for quick removal from the top bracket by a simple operation of the rim cylinder when a clear, unobstructed large opening is required. Once the mullion is removed,

carts, gurneys, large machinery and the like can freely pass through the opening. When the mullion is re-installed, the unit will self lock in place without the need for the key. Each keyed removable mullion set includes top and bottom bracket set, mullion tube, and shims. Rim Cylinder is sold separately.

SPECIFICATIONS – 9200 SERIES


TUBE DIMENSIONS: 2" W x 3" D / 1/8" wall thickness / 11 Gauge steel tube
SIZE: 8' and 10' sizes available in Fire and Non-Fire Rated styles
COLOR: Gray Baked Powder Coating
CERTIFICATION: UL Rated by UL 10B / UL10S standard
WARRANTY: One (1) year limited warranty




REPLACEMENT PARTS

PART	DESCRIPTION
Non Fire Rated Replacement Parts	
929037	Top Bracket
929038	Bottom Bracket
929012	Strike kit with Rim Strike and Strike Hook
929001	Anchors/Expansion
929039	Screw Pack w/Shims
Fire Rated Replacement Parts	
929037F	Top Bracket
929038F	Bottom Bracket
929012F	Strike Kit
929001F	Anchors/Expansion
929039F	Screw Pack w/Shims


ACCESSORIES



TOP BRACKET-929037



BOTTOM BRACKET-929038



MULLION STRIKE KIT-929012F

9200 SERIES

