



- ▶ COMMUNITY PLANNING
- ▶ HOUSING & COMMUNITY DEVELOPMENT
- ▶ EMERGENCY MANAGEMENT
- ▶ OFFICE OF THE SECRETARY



Product Approval

USER: Public User

[Product Approval Menu](#) > [Product or Application Search](#) > [Application List](#) > **Application Detail**

FL #	FL3262-R2
Application Type	Revision
Code Version	2007
Application Status	Approved
Comments	
Archived	
Product Manufacturer	PDQ Manufacturing
Address/Phone/Email	PO Box 507 2754 Creek Hill Road Leola, PA 17540 (717) 656-4281 Ext 25 andyzook@pdqlocks.com
Authorized Signature	Andrew Zook andyzook@pdqlocks.com
Technical Representative	
Address/Phone/Email	
Quality Assurance Representative	

Address/Phone/Email

Category

Exterior Doors

Subcategory

Exterior Door Components

Compliance Method

Certification Mark or Listing

Certification Agency

Intertek Testing Services NA Inc. - ETL/Warnock Hersey

Validated By

Intertek - ETL/Warnock Hersey

Referenced Standard and Year (of Standard)

Standard

Year

ANSI A250.13

2003

ASTM E1886

2002

ASTM E330

2002

Equivalence of Product Standards

Certified By

Product Approval Method

Method 1 Option A

Date Submitted

04/09/2009

Date Validated

05/28/2009

Date Pending FBC Approval

06/10/2009

Date Approved

08/11/2009

Summary of Products

FL #	Model, Number or Name	Description
3262.1	GP Series Cylindrical Lockset	Heavy Duty Grade 2 Cylindrical Lockset
<p>Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: +685/-685 Other: LISTED WINDSTORM RESISTANT PRODUCT ANSI A250.13-2003 ASTM E 1886-2002 ASTM E330-2002 IMPACT RATINGS: OUTSWING - 350 FT-LBS INSWING - N/R DESIGN LOAD RATING - 685 LBF NOT TO BE USED IN THE HVHZ</p>		<p>Certification Agency Certificate FL3262_R2_C_CAC_ANSI_A250.13_Equivalency_Letter.pdf FL3262_R2_C_CAC_PDQ_GP_ATM_Report.pdf Quality Assurance Contract Expiration Date 12/31/2020 Installation Instructions PTID_3262_I_GP_1.pdf PTID_3262_I_GP_2.pdf Verified By: Intertek Testing Services NA Inc. - ETL/Warnock Hersey Created by Independent Third Party: Evaluation Reports Created by Independent Third Party:</p>
3262.2	GT Series Cylindrical Lockset	Extra Heavy Duty Grade 1 Cylindrical Lockset
<p>Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: No Design Pressure: +1485/-1485 Other: LISTED WINDSTORM RESISTANT PRODUCT ANSI A250.13-2003 ASTM E 1886-2002 ASTM E330-2002 IMPACT RATINGS: OUTSWING - 350 FT-LBS INSWING - N/R DESIGN LOAD RATING - 1485 LBF NOT TO BE USED IN THE HVHZ</p>		<p>Certification Agency Certificate FL3262_R2_C_CAC_ANSI_A250.13_Equivalency_Letter.pdf FL3262_R2_C_CAC_PDQ_GT_ATM_Report.pdf Quality Assurance Contract Expiration Date 12/31/2020 Installation Instructions FL3262_R2_II_PTID_3262_I_GT_1.pdf FL3262_R2_II_PTID_3262_I_GT_2.pdf Verified By: Intertek Testing Services NA Inc. - ETL/Warnock Hersey Created by Independent Third Party: Evaluation Reports Created by Independent Third Party:</p>
3262.3	KM Series Deadbolt	Heavy Duty Deadbolt

Limits of Use
Approved for use in HVHZ: No
Approved for use outside HVHZ: Yes
Impact Resistant: Yes
Design Pressure: +2418/-2418
Other: LISTED WINDSTORM RESISTANT PRODUCT ANSI A250.13-2003 ASTM E 1886-2002 ASTM E330-2002 IMPACT RATINGS: OUTSWING - 350 FT-LBS INSWING - N/R DESIGN LOAD RATING - 2418 LBF NOT TO BE USED IN THE HVHZ

Certification Agency Certificate
[FL3262_R2_C_CAC_ANSI_A250.13_Equivalency_Letter.pdf](#)
[FL3262_R2_C_CAC_PDQ_KM_ATM_Report.pdf](#)
Quality Assurance Contract Expiration Date
 12/31/2020
Installation Instructions
[FL3262_R2_II_PTID_3262_I_KM.pdf](#)
 Verified By: Intertek Testing Services NA Inc. - ETL/Warnock Hersey
 Created by Independent Third Party:
Evaluation Reports
 Created by Independent Third Party:

3262.4

MR Series Mortise Lockset

Heavy Duty Grade 1 Mortise Lock

Limits of Use
Approved for use in HVHZ: No
Approved for use outside HVHZ: Yes
Impact Resistant: Yes
Design Pressure: +2453/-2453
Other: LISTED WINDSTORM RESISTANT PRODUCT ANSI A250.13-2003 ASTM E 1886-2002 ASTM E330-2002 IMPACT RATINGS: OUTSWING - 350 FT-LBS INSWING - N/R DESIGN LOAD RATING - 2453 LBF NOT TO BE USED IN THE HVHZ

Certification Agency Certificate
[FL3262_R2_C_CAC_ANSI_A250.13_Equivalency_Letter.pdf](#)
[FL3262_R2_C_CAC_PDQ_MR_ATM_Report.pdf](#)
Quality Assurance Contract Expiration Date
 12/31/2020
Installation Instructions
[FL3262_R2_II_PTID_3262_I_MR_esc.pdf](#)
[FL3262_R2_II_PTID_3262_I_MR_sec.pdf](#)
 Verified By: Intertek Testing Services NA Inc. - ETL/Warnock Hersey
 Created by Independent Third Party:
Evaluation Reports
 Created by Independent Third Party:

[Back](#)

[Next](#)