

FAST ORDER FORM PAGE 1



12 Piece Minimum Order Required

| Customer Order Number | | Ship Via | | Page _____ of _____ | |
|---|--------|--------------------|-------------------------|---------------------|-----------|
| Name | | Ship To | | Date | Territory |
| City | | | | Order Number | |
| State | | Zip | Customer Account Number | | |
| Job Name | | Customer Signature | | | |
| Keying Instructions | | | | | |
| ORDER QTY | FINISH | ANSI FUNCTION | FUNCTION | PDQ PART NUMBER | |
| NON-DEADBOLT FUNCTIONS-SECTIONAL TRIM | | | | | |
| | | F01 | Passage | MR 126 | |
| | | F22 | Privacy | MR 176 | |
| | | F07 | Storeroom | MR 115 | |
| | | F04 | Entrance | MR 116 | |
| | | F05 | Classroom | MR 116 | |
| DEADBOLT FUNCTIONS-SECTIONAL TRIM | | | | | |
| | | F13 | Corridor | MR 136 | |
| | | NA | Entrance | MR 154 | |
| | | F34 | Classroom Security | MR 157 | |
| | | F20 | Dormitory | MR 162 | |
| NON-DEADBOLT FUNCTIONS-ESCUTCHEON TRIM | | | | | |
| | | F01 | Passage | MR 126 | |
| DEADBOLT FUNCTIONS-ESCUTCHEON TRIM | | | | | |
| | | F13 | Corridor | MR 136 | |
| | | NA | Entrance | MR 154 | |
| | | F34 | Classroom Security | MR 157 | |
| | | F20 | Dormitory | MR 162 | |
| GRADE 1 CYLINDRICAL LOCKS — NON KEYED FUNCTIONS | | | | | |
| | | NA | Communicating | GT 125 | |
| | | F75 | Passage | GT 126 | |
| | | F76 | Privacy | GT 176 | |



FAST ORDER FORM PAGE 2



12 Piece Minimum Order Required

| ORDER QTY | FINISH | ANSI FUNCTION | FUNCTION | PDD PART NUMBER | ORDER QTY | FINISH | CERTIFICATION | FUNCTION | PDD PART NUMBER |
|---|--------|---------------|--------------------|-----------------|---|--------|--|--|-----------------|
| GRADE 1 CYLINDRICAL LOCKS — KEYED FUNCTIONS | | | | | CLOSERS | | | | |
| | | F86 | Storeroom | GT 115 | | | UL and ULC listed ANSI A156.4 Grade 1 / Complies with UL 10C and UBC 7.2 (1997) | Closer, Non Sized 3-6 | 1100 BCPA 689 |
| | | F81 | Privacy | GT 116 | | | UL and ULC listed ANSI A156.4 Grade 1 / Complies with UL 10C and UBC 7.2 (1997) | Closer, Non Sized 3-6, SNB | 3101 BCPA 689 |
| | | F110 | Classroom Security | GT 135 | | | | | |
| | | F84 | Classroom | GT 148 | | | | | |
| | | F90 | Dormitory | GT 165 | | | | | |
| | | F82 | Entry | GT 182 | | | | | |
| GRADE 2 CYLINDRICAL LOCKS — NON KEYED FUNCTIONS | | | | | GRADE 2 CYLINDRICAL LOCKS — KEYED FUNCTIONS | | | | |
| | | NA | Communicating | GP 125 | | | UL and ULC listed / Complies with UL 10C and UBC 7.2 (1997) / requirements of ANSI A156.4-2000 Grade 1 / Meets the requirements of ANSI A117.1 and ADA | Closer, non-sized 1-6, full cover, SNB | 5101 BCPA 689 |
| | | F75 | Passage | GP 126 | | | | | |
| | | F76 | Privacy | GP 176 | | | | | |
| | | NA | Single Dummy | GP 211 | | | | | |
| | | F86 | Storeroom | GP 115 | | | UL and ULC listed / Complies with UL 10C and UBC 7.2 (1997) / Certified ANSI A156.4-2000 Grade 1 / Meets the requirements of ANSI A117.1 and ADA | Closer, non-sized 1-6, streamline cover, SNB | 5301 BCPA 689 |
| | | F81 | Entrance | GP 116 | | | | | |
| | | F84 | Classroom | GP 148 | | | | | |
| | | F82 | Entry | GP 182 | | | | | |



FAST ORDER FORM PAGE 3

12 Piece Minimum Order Required



| Customer Order Number | | Ship Via | | Page | | of | | | |
|-----------------------|--------|--|--|----------------------|--------------|-----------|--|---|-----------------|
| Name | | Ship To | | Date | | Territory | | | |
| City | | | | Order Number | | | | | |
| State | | Zip | | Customer Code Number | | | | | |
| Job Name | | Mark Shipment | | Customer Signature | | | | | |
| Keying Instructions | | | | | | | | | |
| ORDER QTY | FINISH | CERTIFICATION | FUNCTION | PDQ PART NUMBER | ORDER QTY | FINISH | CERTIFICATION | FUNCTION | PDQ PART NUMBER |
| CLOSERS (CONT) | | | | | EXIT DEVICES | | | | |
| | | UL and ULC listed / Complies with UL 10C and UBC 7.2 (1997) / Certified ANSI A156.4-2000 Grade 1 / Meets the requirements of ANSI A117.1 and ADA | Closer, non-sized 1-6 Full Cover, SNB | 5501 BCPA 689 | | | UL/ULC listed for "Panic", "Fire Exit Hardware" labeled for up to 1-1/2 hour for 3'0" x 7'0" maximum | Exit, rim, UL panic listed, hex key dogging, 3'0" door | 4200R 689 |
| | | UL and ULC listed / Complies with UL 10C and UBC 7.2 (1997) / Conforms to the requirements of ANSI A156.4-2000 Grade 1 / Meets the requirements of ANSI A117.1 and ADA | Closer, non-sized 1-6, full cover, SNB | 7101 BCPA 689 | | | UL/ULC listed for "Panic", "Fire Exit Hardware" labeled for up to 1-1/2 hour for 3'0" x 7'0" maximum | Exit, surface vertical rod, UL panic listed, hex key dogging, 3'0" door | 4200V 689 |



