



Commercial Full Feature Closer Grade 1

# 5100 Series

# 5100 Series



## Pivot Stop Arm



The Pivot Stop Arm (PS) is designed to serve as a medium-duty door stop for situations where a door stop or overhead stop is not practical. PS uses backcheck to slow the door and a stop that is integrated into the closer arm to limit the travel of the door (integral stop). PS is available in Regular and Top Jamb mounting. Templating is available for opening angles from 85 - 100 degrees in 5-degree increments.

## Spring Cushion Stops



630 SATIN STAINLESS STEEL

613E DARK OXIDIZED SATIN BRONZE (EQUIVALENT)

605 BRIGHT BRASS

PDQ's SCS Series Spring Cushion Stop helps reduce wear and tear on the opening. As the door begins moving through backcheck to its maximum opening angle, the stop acts as a shock absorber, dampening the impact forces.

## Specifications



<b>BODY:</b>	• High Strength Aluminum Alloy Body
<b>ARM OPTIONS:</b>	<ul style="list-style-type: none"> <li>• PA – Parallel Arm</li> <li>• HO – Hold Open</li> <li>• DS/DSHO – Heavy Duty Parallel Arm Stop</li> <li>• RA – Regular Arm</li> <li>• SCS/SCSHO – Heavy Duty Parallel Arm Cushion Stop</li> <li>• TA/TAHO – Track Arm</li> <li>• EDA/EDAHO – Extra Duty Parallel Arm</li> <li>• PS – Pivot Stop Arm</li> </ul>
<b>PISTON:</b>	• Hardened steel, 1-1/2" diameter
<b>ADJUSTMENT:</b>	• Hydraulic controlled closing    • Separate hydraulic backcheck standard    • Optional delayed action (in addition to backcheck)
<b>SIZE:</b>	• Adjustable 1 through 6
<b>MOUNTING:</b>	<ul style="list-style-type: none"> <li>• Tri-packed for regular, top jamb and parallel arm installations</li> <li>• Includes sex nuts/bolts and screws for wood/metal doors/frames</li> <li>• Self drilling, self tapping screws standard</li> <li>• Separate limiting stop may be required for high abuse application</li> </ul>
<b>COVER:</b>	• Full plastic cover standard, optional full metal cover available
<b>FINISHES:</b>	• 605 – Polished Brass, 625 – Polished Chrome, 689 – Aluminum, 693 – Black, 695 – Duro Bronze, 696 – Gold
<b>WARRANTY:</b>	• Twenty-five (25) year Limited Warranty
<b>CERTIFICATIONS, LISTINGS, COMPLIANCES:</b>	<ul style="list-style-type: none"> <li>• UL listed for labeled swinging fire doors rated up to and including 3 hours</li> <li>• Certified to ANSI/BHMA A156.4 Grade 1</li> <li>• TAA compliant. Country of origin: KR</li> </ul>

## Finishes

### Architectural




605 (US3)  
Bright Brass



626 (US26D)  
Satin Chromium

### Painted



689 (US28)  
Aluminum



693  
Black



695  
Dark Duranodic  
Bronze



696  
Gold

Finishes shown are representative only. PDQ cannot guarantee that product shipped will match finishes shown. Not all products are available in all finishes listed.

## Features

- 6 Additional Spring Settings that Provide 17% More Adjustment Capability to Find that Sweet Spot for Optimal Door Closing Action.

## Typical Applications

- Aluminum Storefronts
- Government Facilities
- Higher Education
- Hospitality
- Houses of Worship
- Interior Office Doors
- Multi-family
- Offices
- Retail

## How to Order

QUANTITY	SERIES	DELAYED ACTION	BACKCHECK	ARM TYPE	FINISH	ACCESSORIES
10	51	01	BC	PA	689	—
<b>NOTES</b> 1 - Hold Open (HO) option not permitted for use on labeled fire doors. 2 - Separate limiting stop may be required.		<b>01</b> – Non-Delayed Action <b>41</b> – Delayed Action (In Addition To Backcheck)	<b>BC</b> – Adjustable Hydraulic Backcheck	<b>DS</b> – Door Saver Arm <b>DSHO</b> – Door Saver Hold Open Arm <b>EDA</b> – Extra Duty Arm <b>EDA HO</b> – Extra Duty Arm Hold Open <b>HO</b> – Hold Open, Tri-Pack <b>PA</b> – Tri-Pack (standard) <b>RA</b> – Regular Arm <b>SCS</b> – Spring Cushion Stop <b>SCSHO</b> – Spring Cushion Stop Hold open <b>TA</b> – Track Arm <b>TAHO</b> – Track Arm Hold Open <b>DA</b> – Delayed Action <b>PS</b> – Pivot Stop Arm	<b>605</b> – Polished Brass <b>626</b> – Satin Chromium <b>689</b> – Aluminum <b>693</b> – Black <b>695</b> – Duro Bronze <b>696</b> – Gold	<b>BP</b> – Back Plate <b>BS</b> – Blade Stop Spacer <b>DPPA</b> – Parallel Arm Drop Plate <b>DPTJ</b> – Top Jamb Drop Plate <b>FCM</b> – Full Metal Cover specify hand <b>NFB</b> – Narrow Frame Bracket <b>SDST</b> – Self Drilling Self Tapping Screws

## Size Selector

APPLICATION	CLOSER SIZE	INTERIOR	EXTERIOR
Regular / Top Jamb	1	30"	—
	2	34"	26"
	3	38"	30"
	4	48"	36"
	5	54"	42"
	6	60"	48"
Parallel Arm	1	—	—
	2	30"	—
	3	34"	26"
	4	38"	30"
	5	48"	36"
	6	54"	42"

Note: 5100 Series Closer sizes may vary due to site conditions.

## Cross Reference


MANUFACTURER	PDQ	CAL ROYAL	CORBIN/RUSSWIN®	DORMA	FALCON	HAGER	DORMA COMMERCIAL	LCN®	NORTON®	SARGENT®	ACCENTRA
SERIES	5100	900	N/A	7414-7436	SC60	N/A	N/A	1370	160	1130/1131	51
MOUNTING HOLE PATTERN RETRO-FIT	YES	YES	NO	NO	—	YES	—	NO	NO	NO	NO

Information on this sheet is compiled from public documents and third parties. As a result, PDQ makes no guarantees as to their accuracy, content, quality or availability. Comparisons were made using the technical features only and are not commercial comparisons. Final suitability should be determined by a professional hardware consultant.

## Mounting Position


### Regular Arm (RA)

Regular arm mount is a pull side application with double lever arm. The closer mounts on the door and the arm mounts to the frame. It provides the most efficient operation for door control and is commonly used on in-swing doors from corridors or other interior doors. Regular arm mount is a poor choice for exterior out-swinging doors as it would put the closer on the exterior of the building. The arm assembly projects directly out from the frame. That may be a concern for vandalism or aesthetics. Regular arm application can be used with non-hold open or hold open arms.




### Top Jamb Mount

Top jamb mount is a push side double lever arm application that offers the best alternative to regular arm mount. The closer mounts to the frame and the arm mounts to the door. This application is commonly used on exterior out-swinging doors. It is a poor application for in-swinging doors from a corridor as it places the closer arm in a visible application projecting into the corridor. The arm projects out similar to regular arm mount. Therefore, it can be a concern for vandalism or aesthetics. Top jamb application can be used with non-hold open or hold open arms.



### Parallel Arm (PA)

Parallel arm mount is a push side double lever arm application. The closer is installed on the push side of the door and the arm is mounted to a parallel arm adapter plate installed to the frame soffit. The arm is approximately parallel with the face of the door, eliminating the projection condition evident with regular arm and top jamb applications. Parallel arm is often preferred where aesthetics or vandalism are concerns. Parallel arm is less efficient than regular or top jamb mounts due to the geometry of the arm. Parallel arm application can be used with non-hold open or hold open arms.





### Parallel Stop Arm (DS/DSHO) Extra Duty PA Arm (EDA/EDAHO)

The parallel stop arm mount is an enhanced version of the parallel arm application. It is similar to the parallel arm mount but incorporates a heavy duty rigid arm and soffit plate with limiting dead stop. The dead stop feature is field handed. The closer's backcheck function should be adjusted to cushion the impact of the stop. The parallel stop arm is intended for use where an auxiliary stop cannot be utilized. The parallel stop arm is available in non-hold open (DS) and hold open (DSHO) applications.




**Recommend using the SCS Spring Cushion Stop for moderate to high abuse installations.**

For Extra Duty PA Arm applications, specify EDA or EDAHO. Similar to DS/DSHO without the stop. Requires separate limiting stop by others.



### Track Arm (TA)


The non-handed Track Arm mount incorporates a single stamped arm not designed to be used as a limiting dead stop. Its low profile helps to eliminate projecting arm conditions, which can reduce vandal damage.




### Pivot Stop Arm (PS)

The PS (Pivot Stop) arm is designed to serve as a medium-duty door stop for situations where a door stop or overhead stop is not practical. Available in Regular and Top Jamb mounting, the PS arm uses backcheck to slow the door and a stop integrated into the closer arm to limit the travel of the door. The PS arm limits the travel of the door to a specific, templated angle. Templating is available for opening angles from 85 to 110 degrees in 5 degree increments. The PS arm is not available with hold-open.


## Arms




**RA** - REGULAR ARM




**DS** - DOOR SAVER (LIMITING STOP) ARM




**DSHO** - DOOR SAVER (LIMITING STOP) HOLD OPEN ARM




**HO** - HOLD OPEN ARM




**EDA** - EXTRA DUTY ARM




**EDAHO** - EXTRA DUTY ARM HOLD OPEN




**TA** - TRACK ARM ASSEMBLY




**TAHO** - TRACK ARM HOLD OPEN



**PS** - PIVOT STOP ARM




**PA** - PARALLEL ARM BRACKET




**PAHO** - PARALLEL ARM HO BRACKET


## Accessories




**BP** - BACK PLATE




**BS** - BLADE STOP SPACER




**DPPA** - PARALLEL ARM DROP PLATE



**DPTJ** - TOP JAMB DROP PLATE




**NFB** - NARROW FRAME BRACKET




**SDST** - SELF DRILLING SELF TAPPING SCREWS


## Mounting Plates




**BP** - BACK PLATE




**DPTJ** - TOP JAMB DROP PLATE



**DPPA** - PARALLEL ARM DROP PLATE




**BS** - BLADE STOP SPACER




**NFB** - NARROW FRAME BRACKET

## Covers



**FC** - FULL PLASTIC COVER-5500 (STANDARD)



**FMC** - FULL METAL COVER (OPTIONAL)

## Suggested Architectural Specifications

All door closers shall be PDQ Industries, Inc. 5100 Series with full rack and pinion construction, heavy duty cast aluminum closer body, stamped flat style arm assembly and full architectural cover. Hydraulic control shall be through separate hex-key non-critical sweep, latch and backcheck adjustment. Optional delayed action to be effective from maximum opening to approximately 70 degrees. Closers shall be non-handed, suitable for regular, top jamb and parallel arm applications with fasteners for wood or metal doors and frames. Sex nuts and bolts shall be furnished standard. Spring adjustment to be provided throughout a range of sizes 1-6. All products carry a 25-year manufacturer's limited warranty. Closers shall be UL 10C listed for positive pressure and certified to ANSI/BHMA A156.4-2006 Grade 1.



# SECURING CONFIDENCE OPENING POSSIBILITIES

**Phone:** 717.656.4281

**Tech Support:** 800.441.9692

**Email:** [help@pdqlocks.com](mailto:help@pdqlocks.com)

**Headquarters:** 2230 Embassy Drive, Lancaster, PA  
17603 P.O Box 6426, Lancaster, PA 17607

**Regional Distribution Centers:** Lancaster, PA | Norcross,  
GA | Auburn, WA

**Middle East Manufacturing:** Dammam, Kingdom of  
Saudi Arabia