

Mortise Exit Device

Architectural Submittal Sheet









Specifications

Specifications	ADA COMPLIANT					
Rail:	• Extruded aluminum					
Latch:	Stainless steel dead locking with 3/4" throw					
Hand:	• Field reversible					
Dogging:	Hex key dogging standard Cylinder dogging optional Dogging not available for fire labeled devices					
Minimum Stile Width:	•5"					
Door Thickness:	• 1-3/4* - 2*					
Door Width:	• 24*, 36", 48* standard					
Door Height:	• Panic - Up to 10' • Fire - See fire ratings charts in price book					
Strike Options:	• Default ASA (4-7/8")					
Finishes:	• 605 - Polished Brass, 606 - Satin Brass, 613E - Dark Oxidized Satin Bronze (Equivalent), 622 - Flat Black, 626 - Satin Chrome, 630 - Satin Stainless Steel, 630F - Full Stainless Steel • Optional Anti Microbial Coating available on 626 & 630					
Fasteners:	Includes machine screws and wood screws					
Warranty:	• Ten (10) year limited warranty					
Electrified Options:	Motorized Latch Retraction Request to Exit/Signal Switch Alarmed Exit Latch Bolt Monitor ISMC Connectors Delayed Egress					
Certifications, Compliances, Listings:	Compliances, Compliances, and Usable Buildings					

6300M Series

6300M Mortise Exit Devices

PART	DESCRIPTION
6300M	Mortise wide stile exit, Listed to UL305 for Panic, hex key dogging, 3'0" door width
6300MF	Mortise wide stile exit, Listed to UL10C for Fire, 3'0" door width
6310M	Mortise wide stile exit, Listed to UL305 for Panic, hex key dogging, 4'0" door width
6310MF	Mortise wide stile exit, Listed to UL10C for Fire, 4'0" door width
6320M	Mortise wide stile exit, Listed to UL305 for Panic, no dogging, 2'0" door
6320MF	Mortise wide stile exit, Listed to UL10C for Fire, no dogging 2'0" door

6300M Mortise Mechanical Options

PART	DESCRIPTION
EC	End Cap Cover
TLA	Head Cover (Similar to 6200 Series)
AM	Anti Microbial (630/626 only)
CD	Cylinder Dogging
LD	Less Dogging
SNB	Sex Nuts & Bolts
SHS	Tamper Proof Security Head Screws

6300M Mortise Electrical Options

PART	DESCRIPTION	
AL	Alarmed Exit	
LM	Latch Bolt Monitoring	
MLR	Motorized Latch Retraction	
SS	Signal Switch - Request to Exit and Monitoring	
ALHW	Alarmed Exit with Hard Wire Power and Relay	
ISMC	Industry Standard Molex Connector (order in addition to other electrified options)	
DE	Delayed Egress	

^{1:} Electrified options not available on 24" device.

^{2:} For the MLR Motorized Latch Retraction option: 3 ft devices, maximum cut is 3". 4 ft devices, maximum cut is 9".


^{3:} For the Alarm option: 3 ft devices, maximum cut is 2". 4 ft devices, maximum cut is 8".

6300M Series

6300MF Mortise Devices

		RATING	MAX OPENING	APPLICATION
0	Single Door	90 Minute Rated	4' x 8' Door	

6300 Series Wide Stile





6300M Series

Finishes

605

Bright Brass

Gold anodized aluminum rail (matte), push bar sides and dogging filler Polished brass plated cast head cover and end caps. Polished brass plated heavy gauge stamped push bar face.

606

Satin Brass

Gold anodized aluminum rail (matte), push bar sides and dogging filler Brushed brass plated cast head cover and end caps. Brushed brass plated heavy gauge stamped push bar face.

613F

Dark Oxidized Satin Bronze (Equivalent)

Dark bronze anodized aluminum rail, push bar sides and dogging filler Powder coated cast head cover and end caps. Powder coated heavy gauge stamped push bar face.

622

Flat Black

Black anodized aluminum rail, push bar sides and dogging filler Powder coated cast head cover and end caps. Powder coated heavy gauge stamped push bar face

625

Bright Chrome

Clear anodized aluminum rail (matte), push bar sides and dogging filler Polished chrome plated cast head cover and end caps. Polished chrome plated heavy gauge stamped push bar face.

626

Satin Chrome

Clear anodized aluminum rail (matte), push bar sides and dogging filler Brushed chrome plated cast head cover and end caps. Brushed chrome plated heavy gauge stamped push bar face.

630

Satin Stainless

Clear anodized aluminum rail (matte), push bar sides and dogging filler Plated (stainless look) cast head cover and end caps. Brushed stainless heavy gauge stamped push bar face.

630F

Full Satin Stainless

Brushed stainless fully clad rail, push bar and dogging filler Plated (stainless look) cast head cover and end caps.

