

# XGT/GT 135LED

# Grade 1 Heavy Duty Cylindrical Lock 135LED Series Classroom Intruder

## Architectural Submittal Sheet

### Classroom Intruder Functions

- Easy-to-read LED indicator confirms the door is locked from inside the classroom.
- Arrow shows the direction to turn the key for rapid lockdown, especially helpful in a panic situation.



### Specifications




<b>FOR DOORS:</b>	• 1-3/4" to 2-1/4" thick • Preset for 1-3/4" door
<b>APPLICATION:</b>	• Through door thru-bolting
<b>DOOR PREP:</b>	• Standard ANSI A156.115 (161) for Cylindrical Locks
<b>BACKSET:</b>	• 2-3/4" • Heavy duty diecast, investment cast, chromated cold rolled steel and stainless steel mechanism. Billet Steel spindles for locking functions
<b>FRONT:</b>	• 2-1/4" x 1-1/8" • Stainless Steel or Wrought Brass • Beveled 1/8" in 2"
<b>STRIKE:</b>	• ASA standard • T-Strike or Full Lip Strike optional • Stainless Steel or Wrought Brass
<b>LEVERS:</b>	• Philadelphia (SFL and LFL), Boston (SFL), Miami (SFL)
<b>ROSE:</b>	• 3-3/8" DIA Wrought
<b>LATCHBOLT:</b>	• 9/16" Throw Deadlocking
<b>HAND:</b>	• Non-handed
<b>TRIM:</b>	• Solid diecast PHL, BSN or MIA Levers • 41° Lever Rotation Standard with 2-3/4" Backset • Wrought Brass Roses, Concealed Screws • 65° Lever Rotation Standard with 2 3/4" latch for double doors
<b>KEYS:</b>	• Two (2) per Lock
<b>KEYWAYS</b>	• SCC standard (Schlage C Compatible) • Also available in keyways of other manufacturers
<b>INTERCHANGEABLE CORE:</b>	• Available for all keyed functions • 6 or 7-pin • Large Format IC Core available for PHL Lever ONLY. • Compatible with Best, Falcon and Arrow small format IC cores
<b>CYLINDER:</b>	• 6-pin Brass Insert Cylinder keyed to 5-pins • Standard High Security and UL437 Cylinders Available
<b>KEYING:</b>	• Options: MK, CMK or GMK • Zero Bitted (KO), Keyed Different (KD) or Keyed Alike (KA) Can be keyed into existing master key systems
<b>FINISHES:</b>	• 605 (US3), 606 (US4), 612 (US10), 613E, 619 (US15), 622 (US19), 625 (US26), 626 (US26D) • Optional Antimicrobial Coating 626 (USD26D) only‡ • Optional Weatherized Finish for 626 (USD26D) only
<b>CERTIFICATIONS, LISTINGS, COMPLIANCES:</b>	• UL listed for 3 hrs, for single doors up to 4'0" x 8'0" • Certified to ANSI/BHMA A156.2, Grade 1 • California Education Code Compliant (Functions XGT135, XGT135LED, XGT145) • Federal Specification FF-H-10C (Superseded by A156.2) • Approved for Florida HVHZ (High Velocity Hurricane Zone). PDQ Product Approval: FL 21376. Design load rating: ± 70.0 PSF for single door (3' x 7') • Complies with ADA (Americans with Disabilities Act) and ICC/ANSI 117.1 for Accessible and Usable Buildings
<b>WARRANTY:</b>	• Limited Lifetime Warranty
<b>COUNTRY OF ORIGIN:</b>	• Proudly Assembled in the U.S.A. with U.S. and foreign material. Meets requirements of the Buy American Act as a COTS product manufactured in the United States.

‡ Available with antimicrobial powder coating, treated with silver ionic technology that is known to inhibit the growth of microbes.

# XGT/GT Series 135LED

## PDQ Functions

FUNCTION	FUNCTION NUMBER	OUTSIDE   INSIDE	DESCRIPTION	ANSI NUMBER
Vestibule Class Room Security	XGT/GT135		<ul style="list-style-type: none"> <li>Latchbolt operated by lever from either side</li> <li>Key in either lever locks outside lever</li> <li>Key in either lever unlocks outside lever</li> <li>Inside lever always free</li> </ul>	F110



INDICATES RIGID LEVER

## Levers



Philadelphia



Boston



Miami

## Finishes



605 (US3)  
Bright Brass



606 (US4)  
Satin Brass



612 (US10)  
Satin Bronze



613E  
Dark Oxidized  
Satin Bronze  
(Equivalent)



619 (US15)  
Satin Nickel



622 (US19)  
Flat Black



625 (US26)  
Bright Chromium



626 (US26D)  
Satin Chromium

‡ Check for Antimicrobial Coating,  
626 (USD26D) only.