

Architectural Submittal Sheet



Specifications



FOR DOORS:	• 1-3/8" to 1-3/4" thick • Preset for 1-3/4" door
APPLICATION:	• Fits standard 160 and 161 door prep • No additional thru-bolt
BACKSET:	• Adjustable - 2-3/8" - 2-3/4" (Optional UL Listed fire latch has fixed backsets, 2-3/8" or 2-3/4")
CHASSIS:	• Heavy-gauge cold rolled steel mechanism • Dichromated for corrosion resistance
FRONT:	• 1" face width, 1/4" radius with square corner filler for 1-1/8" width.
STRIKE:	• Full Lip Strike standard, ASA and T-Strike optional
LEVERS:	• Philadelphia, Boston, Miami, Memphis and Orlando
ROSE:	• 2-9/16" Diameter Round Rose, 2-15/16" Square Rose
LATCHBOLT:	• Adjustable - 2-3/8" - 2-3/4" latch standard, Optional UL fire-rated 2-3/4" or 2-3/8" fixed latchbolts are available.
HAND:	• Non-handed, for Memphis, swap levers to rehand.
TRIM:	• Solid diecast PHL, BSN, MIA, MEM and ORL levers • Wrought brass roses • Concealed screws
KEYS:	• Two (2) per Lock
KEYWAYS:	• SCC standard (Schlage C Compatible) • Also available in keyways of other manufacturers
INTERCHANGEABLE CORE:	• 6 or 7-pin • Compatible with Best, Falcon & Arrow. Not available with Memphis lever.
CYLINDER:	• 6-pin Brass Insert Cylinder keyed to 5-pins • Standard High Security Cylinders Available
KEYING:	• Options: MK, CMK or GMK / Zero Bitted (KO), Keyed Different (KD) or Keyed Alike (KA) • Can be keyed into existing master key systems
FINISHES:	• 605 (Bright Brass), 606 (US4) Satin Brass, 613E (Oil Rubbed Bronze), 619 (Satin Nickel), 622 (Flat Black), 625 (Bright Chromium), 626 (Satin Chrome)
COMPLIANCES:	• Complies with ADA (Americans with Disabilities Act) and ICC/ANSI 117.1 for Accessible and Usable Buildings
CERTIFICATIONS, LISTINGS:	• Entry function and optional fixed backset latch only. – Certified to ANSI/BHMA 156.2, Grade 2 (fixed backset latch only). – UL listed for single doors up to 4'0" x 8'0" when ordered with UL latchbolt, contact factory for details. • TAA compliant. Country of origin: KR
WARRANTY:	• Three (3) year Limited Warranty

Levers



Philadelphia



Boston



Miami





Memphis



Orlando

SF Series

PDQ Functions

FUNCTION	FUNCTION NUMBER	INSIDE OUTSIDE	DESCRIPTION	ANSI NUMBER
NON KEYED				
Passage	SF126		Latchbolt operated by lever from either side at all times	F75
Privacy Bedroom Bathroom	SF176		- Latchbolt operated by lever from either side or emergency release in outside lever - Outside lever locked by push button on inside - Outside lever unlocked by emergency release from outside, rotating inside lever, or closing door	F76
KEYED				
Storeroom	SF115		- Latchbolt operated from outside by key, inside by lever - Outside lever always fixed - Inside lever always free - Deadlocking (guarded) latchbolt	F86
Entrance	SF116	 Fixed backset, fire rated, BHMA latch included.	- Latchbolt operated by lever from either side or key in outside lever - Outside lever locked by push/turn button on inside - When outside lever is locked by push button on inside – key from outside, or rotating inside lever unlocks outside lever - When outside lever is locked by pushing and turning the button on the inside, key from outside or rotating inside lever retracts latch but does not unlock outside lever - Deadlocking (guarded) latchbolt	F109
DUMMY				
Single Dummy	SF211		- Pull lever one side - No mechanical operation	—



INDICATES RIGID LEVER

Trim



Round Rose



Square Rose

Finishes



605 (US3)
Bright Brass



606 (US4)
Satin Brass



613E (US10B)
Oil Rubbed Bronze



619 (US15)
Satin Nickel



622 (US19)
Flat Black



625 (US26)
Bright Chromium



626 (US26D)
Satin Chromium

SF Series

Schlage J Series Comparison

	PDQ SF SERIES	SCHLAGE J SERIES
Certified to ANSI/BHMA, Grade 2 (fixed backset only)	Yes	No Grade 3
Cylindrical Lock	Yes	No Tubular Lock
Warranty	3 Years	Lifetime Limited
Lever Design Available	7	14
Finishes Available	7	9
Square Rose Available	Yes	Yes
UL Listed	Yes, with fixed latchbolt	Yes, but only for two functions