


# 6202R SERIES

# ARCHITECTURAL NARROW STILE RIM EXIT DEVICE

## ARCHITECTURAL SUBMITTAL SHEET



**RIM**  
ANSI TYPE 4

## SPECIFICATIONS




<b>CHASSIS:</b>	<ul style="list-style-type: none"> <li>Corrosion resistant plated steel</li> </ul>
<b>RAIL:</b>	<ul style="list-style-type: none"> <li>Extruded aluminum</li> <li>Specify 630F for full stainless tactile surfaces (roll formed)</li> </ul>
<b>LATCH:</b>	<ul style="list-style-type: none"> <li>RIM (R) – Pullman with dead latching, stainless steel, 3/4" throw</li> </ul>
<b>HAND:</b>	<ul style="list-style-type: none"> <li>Device is non-handed</li> <li>Trim is non-handed or field reversible</li> </ul>
<b>DOGGING:</b>	<ul style="list-style-type: none"> <li>Hex Key Dogging Standard</li> <li>Dogging not available on Fire Listed Devices</li> <li>Cylinder dogging optional</li> </ul>
<b>MINIMUM STILE WIDTH:</b>	<ul style="list-style-type: none"> <li>2-5/8"</li> </ul>
<b>DOOR THICKNESS:</b>	<ul style="list-style-type: none"> <li>1-3/4" Standard, others vary by trim selection</li> </ul>
<b>DOOR WIDTH:</b>	<ul style="list-style-type: none"> <li>Standard for 3 ft doors option, available for doors up to 4 ft. width.</li> </ul>
<b>FINISHES:</b>	<ul style="list-style-type: none"> <li>613 – Oil Rubbed Bronze, 630 - Stainless Steel, 630F Full Satin Stainless Tactile Surface</li> <li>Optional Anti Microbial Coating available on 630 finish only</li> </ul>
<b>FASTENERS:</b>	<ul style="list-style-type: none"> <li>Includes sex nuts, machine screws and wood screws.</li> </ul>
<b>ELECTRONIC ACCESS CONTROL OPTIONS:</b>	<ul style="list-style-type: none"> <li>Motorized Latch Retraction</li> <li>Request to Exit/Signal Switches SS/SS2</li> <li>Alarmed Exit</li> <li>MLR Retrofit Kit - 81550K-MDT</li> </ul>
<b>WARRANTY:</b>	<ul style="list-style-type: none"> <li>Ten (10) year limited warranty</li> </ul>
<b>CERTIFICATIONS, LISTINGS, COMPLIANCES:</b>	<ul style="list-style-type: none"> <li>UL 305 listed for "Panic", UL10C Listed for "Fire Exit Hardware" up to 3 hours</li> <li>Certified to ANSI/BHMA 156.3, Grade 1</li> <li>Complies with ADA (Americans with Disabilities Act) and ICC/ANSI 117.1 for Accessible and Usable Buildings</li> <li>Meets requirements of the Buy American Act.</li> </ul>

# 6202 SERIES

# ARCHITECTURAL NARROW STILE EXIT DEVICE TRIM


## ARCHITECTURAL SUBMITTAL SHEET

### LEVER STYLES




PHILADELPHIA 

### TRIM TYPES



EN - ESCUTCHEON



GN - GRIP PULL

### TRIM FUNCTIONS

FUNCTION*	DESCRIPTION
01	Exit only, no trim.
02	Entrance by trim when actuating bar is locked down (dummy trim).
03	Entrance by trim when latch is released by key. Key removable only when locked (night latch).
04	Entrance by trim when latch is retracted by key or set in retracted position by key (night latch with cylinder dogging). Requires 6212 device with cylinder dogging.
08	Entrance by knob or lever. Key locks or unlocks knob or lever (classroom lever).
14	Entrance by trim when latch bolt is released by lever. Always active, no cylinder (passage lever).

\*All functions not available in every trim style


### FINISHES

CODE*	DESCRIPTION
613 (US10B)	Oil Rubbed Bronze, No Coating
626 (US26D)	Satin Chromium Plated, No Coating
630 (US32D)	Satin Stainless Steel, No Coating (Grip Pull Trim Only)

\*All finishes not available in every trim style

### HANDING

#### Out Swing Door



LEFT HAND  
REVERSE (LHR)

RIGHT HAND  
REVERSE (RHR)

OUTSIDE

# 6202 SERIES

# ARCHITECTURAL NARROW STILE EXIT DEVICE TRIM

## ARCHITECTURAL SUBMITTAL SHEET

### HOW TO ORDER

QUANTITY	SERIES	TYPE	FUNCTION	LEVER	HANDING	FINISH	CYLINDER OR HOUSING*	KEYWAY*	KEYING*	OPTIONS
10	6	EN	08	PHL	—	626	D	SCC	KD	—
<b>Notes:</b> <b>1 - List price includes standard default cylinder</b>		<b>GN</b> — Grip Pull, Narrow <b>EN</b> — Escutcheon, Narrow Stile	<b>02</b> — Dummy Trim <b>03</b> — Night Latch <b>04</b> — Night Latch w/Exit Device Cylinder Dogging <b>08</b> — Classroom w/Lever <b>14</b> — Passage w/Lever	<b>PHL</b> — Philadelphia	<b>RHR</b> <b>LHR</b>	<b>613</b> — Oil Rubbed Bronze <b>626</b> — Satin Chrome <b>630</b> — Satin Stainless Steel	<b>D</b> — Default <b>L</b> — Less Cylinder <b>SF6</b> — SFIC w/Core, 6 Pin <b>SF7</b> — SFIC w/Core, 7 Pin <b>LF</b> — Schlage® Compatible LFIC w/Core <b>SFL</b> — SFIC Housing less core <b>LFL</b> — Schlage® Compatible LFIC Housing less core	<b>*Standard High Security Cylinders, Cores and Keying Information — See Cylinders, Keying and Cores Architectural Submittal Sheets</b>		<b>AM</b> — Antimicrobial Coating

### TRIM CYLINDER REFERENCE GUIDE

FUNCTION	DESCRIPTION	EN ESCUTCHEON FOR NARROW STILE	GN GRIP PULL, NARROW STILE
03	Night Latch	RIM	RIM
04	Night Latch w/Exit Device Cylinder Dogging	RIM	RIM
08	Classroom w/Lever	Mortise	—





# 6202 SERIES

# ARCHITECTURAL NARROW STILE EXIT DEVICE TRIM

## ARCHITECTURAL SUBMITTAL SHEET

### NARROW STILE TRIM

GEN	APPLICATION	FUNCTION	DESCRIPTION	LEVER	630	613
NARROW ESCUTCHEON  	RIM SURFACE VERTICAL ROD CONCEALED VERTICAL ROD	02	Dummy Trim (Rigid Lever)	PHL	•	•
		03	Night Latch w/Lever		•	•
		08	Classroom w/ Lever		•	•
		14	Passage w Lever		•	•

6GN	APPLICATION	FUNCTION	DESCRIPTION	LEVER	630	613
GRIP PULL    <b>Compatible with Rim (R) and Surface Vertical Rod (SVR) devices only.</b>	RIM SURFACE VERTICAL ROD	02	Dummy Trim		•	
		03	Night Latch		•	

### OPTIONS

CODE	DESCRIPTION
AM	Antimicrobial coating applied to tactile surfaces