



MLR MOTORIZED LATCH RETRACTION

ARCHITECTURAL SUBMITTAL SHEET

WHEN IT'S BETTER TO BE SEEN AND NOT HEARD!!



FEATURES

- Ultra Quiet Operation
- For use with PDQ 6200 Wide Stile or 6202 Narrow Stile exit devices, panic and fire listed.
- Unique motor drive retracts Push Pad.
- Dual operation -maintained or momentary operation.
- Supports remote signaled electric dogging.
- Low power requirements. Interfaces with PDQ's 81440 2A 24VDC Filtered/Regulated Power Supply, and EL Series Electrified Power Transfer Hinges
- Suitable for pairing with Low Energy Power Operators
- Non-polarized leads
- On-board diagnostic LED lights
- UL Listed

81550K-MDT RETROFIT KIT **NEW**

- Designed to field retrofit 6200 and 6202 series exit devices
- Includes motor drive module, connectors and fasteners

ELECTRICAL SPECIFICATIONS

Note: Operating voltage at $\pm 10\%$ of rated voltage.
Input voltage: 24VDC
• Rated in-rush current: 1.0A.
• Operational in-rush current: .85A.
• Continuous current, electric dogging: .4A.
• Recommended Power Supply: PDQ Model # 81440. Input: 120VAC, .9A, 50/60Hz 240VAC, .6A, 50/60Hz Output: 24VDC, 2A, filtered and regulated.

PERFORMANCE

- Motor drive factory tested to over 500,000 cycles (Over 2 times the ANSI/BHMA)