

KT SERIES

Extra Heavy Duty Bored Deadbolts



COMMERCIAL GRADE



Finishes

FOR DOORS:	• 1-3/8" to 1-3/4"
BACKSET:	• 2-3/4" standard • 2-3/8" available
FRONT:	• 2-1/4" x 1-1/8" or 2-1/4" x 1" • Stainless Steel or Wrought Brass
STRIKE:	• 2-3/4" x 1-1/8" • Stainless Steel or Wrought Brass
DEADBOLT:	• 1" Throw • Brass Bolt containing two concealed 1/4" case-hardened Steel Roll Pins
HAND:	• Non-handed
TRIM:	• Wrought Brass Scalp • Reinforced Zinc Diecast Rose
KEYS:	• Two (2) per Lock
KEYWAYS:	• SCC standard (Schlage C Compatible) • Also available in keyways of other manufacturers
CYLINDER:	• 6-pin Brass Mortise Cylinder keyed to 5-pins, SFIC
KEYING:	• Keyed to your needs , Can be MK, CMK, GMK. Available Zero Bitted (KO), Keyed Different (KD), Keyed Alike (KA).
FINISHES:	• 605 (US3), 606 (US4), 612 (US10), 613 (US10B), 625 (US26) or 626 (US26D)
WARRANTY:	• One (1) year Limited Warranty
LISTINGS:	• UL 10C listed, 3-hour fire rated as auxiliary locks for A label single doors • UL 10B listed for neutral pressure doors



KM SERIES

Heavy Duty Bored Deadbolts



COMMERCIAL GRADE



Finishes

FOR DOORS:	• 1-3/8" to 1-3/4" Conventional Cylinder, 1-1/2" to 2" SFIC
BACKSET:	• 2-3/4" standard (UL) • Option - 2-3/4" - 2-3/8" adjustable with 2-1/4" x 1" faceplate available (Not U.L. Listed)
FRONT:	• 2-1/4" x 1-1/8" • Stainless Steel or Wrought Brass
STRIKE:	• 2-3/4" x 1-1/8" • Stainless Steel or Wrought Brass
DEADBOLT:	• 1" Throw • Brass Bolt containing one concealed 1/4" case-hardened Steel Roll Pin.
HAND:	• Non-handed
TRIM:	• Stainless Steel or Wrought Brass Scalp • Reinforced Zinc Diecast Rose
KEYS:	• Two (2) per Lock
KEYWAYS:	• SCC standard (Schlage C Compatible) • Also available in keyways of other manufacturers
SFIC CORE:	• 6 or 7-pin • Compatible with all SFIC cores.
CYLINDER:	• 6-pin Brass RIM Cylinder keyed to 5-pins. • Keyed to your needs , Options: MK, CMK or GMK
KEYING:	• Zero Bitted (KO) or 1 Bitted, Keyed Different (KD) or Keyed Alike (KA) • Can be keyed into existing master key systems
FINISHES:	• 605 (US3), 606 (US4), 613 (US10B), 622 (US19), 626 (US26D) or 630 (US32D) • UL 10C listed, 3-hour fire rated as auxiliary locks for A label single doors • UL 10B listed for neutral pressure doors
CERTIFICATIONS, LISTINGS COMPLIANCES:	• Thumbturn complies with ADA (Americans with Disabilities Act) and ICC/ANSI 117.1 for Accessible and Usable Buildings
WARRANTY:	• One (1) year Limited Warranty

