


## ARCHITECTURAL SUBMITTAL SHEET



**MORTISE CYLINDER DEADBOLT**



## SPECIFICATIONS

<b>FOR DOORS:</b>	• 1-3/4"
<b>BACKSET:</b>	• 2-3/4"
<b>CASE:</b>	• Steel — Dichromated for corrosion resistance
<b>FACEPLATE:</b>	• 1-1/4" x 5-5/8"
<b>FRONT:</b>	• 2-1/4" x 1" • Stainless Steel.
<b>STRIKE</b>	: • 1-1/8" x 2-1/2"
<b>DEADBOLT:</b>	• 1" Throw. • Stainless Steel.
<b>OPTIONAL THUMBTURN:</b>	• ADA Compliant.
<b>HAND:</b>	• Non-handed except for function MJ134 Classroom. (See Function Table and How to Order Guide).
<b>KEYS:</b>	• Two (2) per Lock.
<b>KEYWAYS:</b>	• SCC standard (Schlage C Compatible) • Also available in keyways of other manufacturers
<b>INTERCHANGEABLE CORE:</b>	• 6 or 7-pin • Compatible with Best, Falcon & Arrow • Large Format IC Cores compatible with Schlage.
<b>CYLINDER:</b>	• 6 or 7-pin Mortise Cylinder
<b>KEYING:</b>	• Options: MK, CMK or GMK • Zero Bitted (KO), Keyed Different (KD) or Keyed Alike (KA) • Can be keyed into existing master key systems
<b>FINISHES:</b>	• 630 (US32D) - Satin Stainless Steel
<b>CERTIFICATIONS, LISTINGS, COMPLIANCES:</b>	• UL listed • Meets requirements of the Buy American Act.
<b>WARRANTY:</b>	• 10-Year Limited Warranty

## CROSS REFERENCE\*

ANSI # A156.5 (A156.13)	PDQ FUNCTION	BEST	CORBIN	DORMA	MARKS #31/32/33 SERIES	SARGENT	SCHLAGE	YALE
E06081 (F18)	MJ131	48H L	DL4111	D961	L	4876	L464	353
E06071 (F17)	MJ132	48H K	DL4113	D960	K	4875	L460	352
E06061 (F16)	MJ133	48H M	DL4112	D962	M	4874	L462	351
E06091 (F29)	MJ134LH	48H R	DL4117	D963	S	4877	L463	357
	MJ134LH							

\*Note: Functions are equal, but form may differ.